



G50-S3 Downlight



G50KIT-S3 Downlight



Feature

- Smart design, economic cost
- Standard model with reflector design, light output effect is same with MR16 halogen
- An ideal replacement for 35W halogen, deliver 450-550Lm at only 6W, efficacy 80Lm/W
- The compact module design is compatible with most existing trims for retrofit market
- G50 S3 mounted ring is the most economic model
- G50 KIT is fixed with LED driver box
- 36 and 60 degree beam angle shaped by multi-faceted reflector;
- High quality LED with consistent color temperature
- Mains (TRIAC) dimming as standard.

Material

- Fixture: Aluminium
- Reflector: PC with AL plating
- LED: Bridgelux COB 1 PCS
- Weight: 120g

LED Driver

- LED driver: LED-AC350-8W-DIM
- Dimming: 240v trailing edge mains dimmable


Benefit

- Replace MR16 halogen 35W downlight with 80% energy saving
- Compact size suitable for various application
- Anti-glare reflector achieves comfortable lighting ambient


Application

- shop lighting, accent lighting, office lighting, hotel lighting

Beam Angle Option



Medium Beam
36°



Wide Beam
60°



G50 R5 LED Downlight Module

Replace
Halogen 35W



Weight
120g



G50 R5 LED Downlight Module included
With external driver (*Dimmable or Non-Dimmable*)
Lumen output: 450-550lm

STANDARD MODEL **Ra 83**

Product Code	Lumen output	cd	Beam	Led power	System power	CCT	CRI	LED Brand
EVO-G50-36-3000K	500 lm	970	36°	6 W	8 W	3000K	83	Bridgelux
EVO-G50-36-4000K	550 lm	1090	36°	6 W	8 W	4000K	83	Bridgelux
EVO-G50-60-3000K	500 lm	550	60°	6 W	8 W	3000K	83	Bridgelux
EVO-G50-60-4000K	550 lm	680	60°	6 W	8 W	4000K	83	Bridgelux



Efficiency: 68 lm/W

Life time: 50,000 hours (70% Lumen maintenance)

**Dimmable or
Non-dimmable**

