

MOUNTED RING STYLE



Flush ring

Feature

- E8F is designed with excellent heatsink and flexible installation. The interchangeable mounted ring is twisted&lock; rotatable fixing clip is adaptable to 1-45 mm thickness ceiling as well as greatly illuminate environment
- The high-grade optical diffuser provide uniform light
- IP44 protection
- Different mounted ring styles are optional to fulfill different aesthetic design requirements.
- Lumen Range: 1200-3500 Lm and Wattage Range: 15-50W; Beam Angle:70°

Material

- Fixture: Die-cast Aluminium (Mounted ring color: matt white)
- Diffuser: high grade PMMA (No yellowing in 30 years);
- Weight: 1725g

Benefit

- Achieve comfortable light ambient
- Replace 26W,32W,2*18W,2*26W,2*32W CFL downlight with 50% energy saving
- Replace 35W,70W HID downlight with 30-50% energy saving

Application

- Shop lighting,general lighting

OPTION



Emergency Kit



E8F LED Downlight




IP44



UGR
< 19

Weight
1725g



E8F LED Downlight Series
With external driver (*Dimmable or Non-Dimmable*)
Lumen output: 1200-3500lm


STANDARD MODEL

Product Code	Lumen output	Led power	System power	CCT	CRI	LED Brand
LED-EVOE8F-22W-3K	3000 lm	32 W	35 W	3000K	85	Samsung
LED-EVOE8F-22W-4K	3000 lm	32 W	35 W	4000K	85	Samsung
LED-EVOE8F-22W-55K	3000 lm	32 W	35 W	5500K	85	Samsung



Efficiency: 78 lm/W

Life time: 50,000 hours (70% Lumen maintenance)

3 Years Guarantee



LED-EVOE8F-22W-3K



	0	90
0	1168	1168
5	1150	1150
15	1054	1054
25	903	903
35	668	668
45	418	418
55	227	227
65	106	106
75	35	35
85	0	0

