



Feature

- E6F is designed with excellent heatsink and flexible installation. The interchangeable mounted ring is twisted&lock; rotatable fixing clip is adaptable to 1-35 mm thickness ceiling
- The high-grade optical diffuser provide uniform light as well as greatly illuminate environment
- Different mounted ring styles are optional to fulfill different aesthetic design requirements
- Lumen Range: 1200-2500 Lm and Wattage Range: 15-38W; Beam Angle:70°.

Material

- Fixture: Die-cast Aluminium (Mounted ring color: matt white)
- Diffuser: high grade PMMA (No yellowing in 30 years);
- Weight: 1300g

Benefit

- Achieve comfortable light ambient
- Replace 26W,32W,2*18W,2*26W CFL downlight with 50% energy saving
- Replace 35W HID downlight with 30-50% energy saving

Application

- shop lighting, general lighting

STANDARD RING STYLE



Stylish ring

OPTION



Emergency Kit

E6R LED Downlight



E6R LED Downlight Series
With external driver (*Dimmable or Non-Dimmable*)
Lumen output: 1200-2500lm


STANDARD MODEL

Product Code	Lumen output	Led power	System power	CCT	CRI	LED Brand
LED-EVOE6R-3K	2000 lm	22 W	26 W	3000K	83	Samsung
LED-EVOE6R-4K	2000 lm	22 W	26 W	4000K	83	Samsung
LED-EVOE6R-55K	2000 lm	22 W	26 W	5500K	83	Samsung



LED Driver

DIMTRONIC™



Efficiency: 80 lm/W
Life time: 50,000 hours (70% Lumen maintenance)
3 Years Guarantee

LED-EVOE6R-3K

