

STANDARD RING STYLE



Stylish ring

Feature

- E8R is designed with excellent heatsink and flexible installation. The interchangeable mounted ring is twisted&lock; rotatable fixing clip is adaptable to 1~45 mm thickness ceiling
- The high-grade optical diffuser and multi-faceted reflector provide softer light for more appealing interiors.. Glare cut-off 25°;UGR<19
- Different mounted ring and reflector styles are optional to fulfill different aesthetic design requirements.
- Lumen Range: 1200-3500 Lm and Wattage Range: 15-50W; Beam Angle:70°

Material

- Fixture: Die-cast Aluminium (Mounted ring color: matt white)
- Diffuser: high grade PMMA (No yellowing in 30 years)
- Reflector: Aluminium with high reflective AL plating
- Weight: 1640g

Benefit

- Achieve comfortable light ambient
- Replace 26W,32W,2*18W,2*26W,2*32W CFL downlight with 50% energy saving
- Replace 35W,70W HID downlight with 30-50% energy saving

Application

- Office lighting, shop lighting,corridor lighting

OPTION



Emergency Kit

E8R LED Downlight



E8R LED Downlight Series
With external driver (Dimmable or Non-Dimmable)
Lumen output: 1200-3500lm


STANDARD MODEL

Product Code	Lumen output	Led power	System power	CCT	CRI	LED Brand
LED-EVOE8R-3K	3000 lm	32 W	35 W	3000K	85	Samsung
LED-EVOE8R-4K	3000 lm	32 W	35 W	4000K	85	Samsung
LED-EVOE8R-55K	3000 lm	32 W	35 W	5500K	85	Samsung



Efficiency: 78 lm/W

Life time: 50,000 hours (70% Lumen maintenance)

3 Years Guarantee



LED-EVOE8R-3K



	0	90
0	1467	1467
5	1437	1437
15	1253	1253
25	979	979
35	674	674
45	324	324
55	91	91
65	13	13
75	1	1
85	0	0

